



**CERT**

# DVGW type examination certificate

## DVGW-Baumusterprüfzertifikat

**DG-4550DO0019**

Registration Number  
Registriernummer

<b>Field of Application</b> <i>Anwendungsbereich</i>	products of gas supply <i>Produkte der Gasversorgung</i>
<b>Owner of Certificate</b> <i>Zertifikatinhaber</i>	ISOTUBI S.L. C/Mecànica 6 Pol. Ind. Santa Rita, E-08755 Castellbisbal (Barcelona)
<b>Distributor</b> <i>Vertreiber</i>	ISOTUBI S.L. C/Mecànica 6 Pol. Ind. Santa Rita, E-08755 Castellbisbal (Barcelona)
<b>Product Category</b> <i>Produktart</i>	Pipe equipment and fittings: Compression joint for metallic gas pipes (4550)
<b>Product description</b> <i>Produktbezeichnung</i>	Compression joint made of stainless steel for pipes made of stainless steel according to GW 541
<b>Model</b> <i>Modell</i>	NUMEPRESS
<b>Test reports</b> <i>Prüfberichte</i>	Type testing: B 23/01/3998 from 10.01.2023 (DBI)
<b>Test basis</b> <i>Prüfgrundlagen</i>	DVGW G 5614 (01.12.2013) DVGW G 5614-B1 (01.06.2016)

**Date of Expiry / File No.** 10.01.2028 / 22-0585-GNE  
*Ablaufdatum / Aktenzeichen*

14.02.2023 Kir A-1/2

Date, Issued by, Sheet, Head of Certification Body  
*Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle*



Deutsche  
Akkreditierungsstelle  
D-ZE-16028-01-05

DVGW CERT GmbH  
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3  
53123 Bonn

Tel. +49 228 91 88 - 888  
Fax +49 228 91 88 - 993

www.dvgw-cert.com  
info@dvgw-cert.com

<b>Gas Category</b> <i>Gasart</i>	<b>Remarks</b> <i>Bemerkungen</i>
Fuel gases according to G 260	

<b>Type</b> <i>Typ</i>	<b>Technical Data</b> <i>Technische Daten</i>	<b>Remarks</b> <i>Bemerkungen</i>
NUMEPRESS	Nominal pressure rating: MOP 5 Nominal diameter: 88,9 mm	
NUMEPRESS	Nominal pressure rating: MOP 5 Nominal diameter: 108 mm	

**certified Components**  
*zertifizierte Bauteile / Werkstoffe*

<b>Registr. No.</b> <i>Registrier-Nr.</i>	<b>Component</b> <i>Bauteil (Produktart)</i>	<b>Model/Type</b> <i>Modell/Typ</i>	<b>Manufacturer</b> <i>Hersteller</i>
NG-5112CL0298	Elastomer material for seals in gas appliances	TEC H16 GI-70 giallo/TEC H16 GI-70 giallo	Tecnogomma International S.p.A.
NG-5113CR0439	Elastomer material for seals in gas supply mains and pipelines	TEC H16 GI.-70 giallo/TEC H16 GI.-70 giallo	Tecnogomma International S.p.A.

**Hints of Utilization / Remarks**  
*Verwendungshinweise / Bemerkungen*

Pipes: Stainless steel according to DVGW G 541, material 1.4404  
 Ambient temperature range: -20...+70 °C  
 Connections: Press connection according to DVGW G 5614, one side also thread according to DIN EN 10226-1 or flanges PN 10 according to DIN EN 1092-1  
 Thread connections according to DIN EN 10226-1 up to R/Rp 2 are permitted up to a max. pressure of 5 bar and threaded connections from R/Rp 2 1/2 are permitted up to a max. pressure of 1 bar.